

Preliminary Product Specifications

Product specifications	P2
Projector type	Single chip DLP solid-state projector
Resolution	2560 x 1600 (WQXGA), 1920 x 1200 (WUXGA)
Brightness	5,000 RGB mode
Contrast ratio	1,600:1 - 8,000:1 sequential, >5,000,000:1 dynamic
Aspect ratio	16:10
Brightness uniformity	90%
Lens options	N1: 0.80 - 1.25:1 @ WQXGA, 0.74 - 1.16:1 @ WUXGA N2: 1.20 - 1.60:1 @ WQXGA, 1.12 - 1.50:1 @ WUXGA
Lens shift (max)	N1: Vertical +/- 68%, horizontal +/- 57.5% @ WQXGA N1: Vertical +/- 56.5%, horizontal +/- 52.5% @ WUXGA N2: Vertical +/- 120.5%, horizontal +/- 85% @ WQXGA N2: Vertical +/- 109%, horizontal +/- 78.5% @ WUXGA
Color correction	P7
Light source (fully sealed optical architecture)	Patent Pending (RGB + optional IR). Standard IR wavelength where applicable is 740 nm, other IR wavelengths available
Illumination lifetime	> 50,000 hours (TBC)
Optical block lifetime	> 100,000 hours
Orientation	Orientation free, no limitation
Inputs	2 x Dual Link DVI, 1 x DisplayPort 1.2, 1 x HDMI 2.0
Input resolutions	2560 x 1600 - 640 x 480. Max Pixel Clock 667MHz
3D	TBC
Latency	19 ms @ 60Hz / 9.5 ms @ 120Hz
Displayable color	30 Bit per channel
Control	IR, RS232, Ethernet, 2 x BNC (sync) & 1 x Mini DIN
Software tools	norxenet
Power requirements	90 - 240V 50-60Hz
Power consumption (max)	650 W typical
Heat dissipation (max)	2220 BTU/hour typical
Ambient noise	32 dB A
Operating temperature	0 - 40°C / 32 - 104°F (0 - 3000m)
Storage temperature	-20 - 60°C / -4 - 140°F
Operating humidity	20 - 80% (non-condensing)
Storage humidity	10 - 90% (non-condensing)
Dimensions: (L x W x H)	500 x 505 x 241 mm / 19.68 x 19.88 x 9.489 inch
Weight	22.5 kg / 49.6 lbs excl. lens
Standard accessories	Power cord EUR & US + local region (where applicable), wireless IR remote control, lens mount and lens lock fixings
Shipping dimensions (L x W x H)	TBC
Shipping weight	TBC
Certifications	CE, FCC Class A, cNemkous, KC, CCC
MTBF	TBC
Warranty	5 years
24/7	Yes

Preliminary Specifications subject to change without prior notice. Errors & omissions exempt.